

Biodiesel Nitrile

Biodiesel is a clean burning alternative fuel produced domestically. Biodiesel is nontoxic, biodegradable and can be used in diesel engines usually with no modifications.

Biodiesel Nitrile is specially designed and developed for use in environments where alternative fuels are present. Immersion test results indicate that these materials are compatible with alternative fuels and are suitable for Bio-Diesel B20 (20% Bio-Diesel and 80% Petroleum Diesel) and Bio-Diesel B100 (100% Bio-Diesel).



Finish: Smooth

Durometer Hardness Shore A ± 5	Thickness Inches	Width Inches	Tensile* psi	Ultimate Elongation* %	Temperature Range	Estimated Weight Per Linear Foot (1/8" x 36")
60	1/32 thru 1/2	36, 48	1500	300	-30°F to +220°F	2.39 lb
70	1/32 thru 1/2	36, 48	1800	250	-30°F to +220°F	2.4 lb

*Typical Values

Physical property values are based on typical values obtained from laboratory test samples. Actual production values may vary. WARCO BILTRITE makes no guarantees as to the suitability and performance of the material for the intended end-use application. Thorough evaluation under end-use application conditions is highly recommended.

visit us at warco.com

WARCO® BILTRITE®

Corporate Office

1337 Braden Court
Orange, California 92868
Tel: 714-532-3355
Fax: 714-532-2238

WARCO®

West American Rubber Company, LLC

Sales, Manufacturing & Distribution

750 North Main Street
Orange, California 92868
Tel: 714-532-3355
Fax: 714-532-2238
Email: Sales@warco.com

BILTRITE®

Biltrite Ripley Operations, LLC

Sales, Manufacturing & Distribution

16310 Highway 15 North
Ripley, Mississippi 38663
Tel: 800-245-8748
Fax: 662-837-0132
Email: BiltriteSales@warco.com